

# INTERLOCKED POWER MODULES

## Catalog Numbering Guide (Industrial)

ESL interlocked power outlets catalog numbers are easily specified using the guide below:

**R200 - 480 - 200 - 65 M E W - SP**

### Receptacle Cover

SP = Snap Cover  
SW = Screw Cover

### Optional Features

P = Pilot Light  
A = Auxiliary Switch  
Etc.

### Receptacle Manufacturer

(Various)

### Interlock Mechanism Model

D = Mechanically Interlocked  
E = Electrically Interlocked

### Faceplate Size

S = 5"X6"  
L = 8"X7"  
M = 10.5"X10"  
X = 12"X10.5"

### Circuit Breaker Interrupting Capacity

10 = 10,000 AIC  
22 = 22,000 AIC  
25 = 25,000 AIC  
35 = 35,000 AIC  
65 = 65,000 AIC  
100 = 100,000 AIC

### Circuit Breaker Trip Rating

20 = 20AMP  
30 = 30AMP  
50 = 50AMP  
60 = 60AMP  
90 = 90AMP  
100 = 100AMP  
150 = 150AMP  
200 = 200AMP  
400 = 400AMP

### Voltage

120 = 120VAC  
240 = 240VAC  
480 = 480VAC

### Receptacle Rating / Configuration

R20 = 20AMP  
R30 = 30AMP  
R60 = 60AMP  
R100 = 100AMP  
R200 = 200AMP  
R400 = 400AMP

